



FLIGHTLINE SUPPORT LTD

1000 LITRES BUNDED AVIATION TOWABLE BOWSER



SPECIFICATION FOR 1000 LITRES BUNDED AVIATION TOWABLE BOWSER

SPECIFICATION INCLUDES:

- Tough, fully baffled 4mm aluminium inner tank, with bolted manway access.
- 110% 4mm aluminium outer bund incorporating roll over protection frame.
- Clear front access to fuel dispensing equipment
- Tough galvanised steel chassis fitted with rear bumper and galvanised mudguards
- Towing hitch with overrun brake linkage, handbrake and heavy duty jockey wheel
- Fully compliant trailer lighting system incorporating side marker lights and 7 pin plug connection
- Fitted with an automatic suction breather, pressure relief valve and pressure vacuum vent/turnover valve
- Water sampling point with lift pump
- Painted in white
- 10 metres of elaflex fuel delivery hose
- High flow diesel engine centrifugal pump
- Monitor filtration – FGO609.
- Fill-rite 4 digit flow meter with reset knob and totaliser
- ZVF-25 high flow aviation refuelling nozzle with mesh strainer
- Earth bonding reel with 15m of high vis bonding cable
- Storage boxes along the sides (hose storage)

WEIGHT

Approx 750kg empty

Approx 1570kg full (using an SG of .82 for JetA1 fuel)

Flightline Support Ltd
Lakeside Industrial Park
Cotswold Dene
Standlake
Witney
Oxfordshire
OX29 7PL
U.K.

Tel +44 (0) 1993 776564
Fax +44 (0) 1993 778953

fsluk.com