



FLIGHTLINE SUPPORT LTD

757 REFUELLING STEPS



INTRODUCTION

Aluminium and stainless-steel construction. Designed to be robust, but light weight and easily manoeuvred by a single operator. 4 off heavy-duty 470mm diameter wheels are used to aid manual manoeuvrability

Typical Dimensions: Length 3.6m, Height 2.6m, Width 1.7m

OPERATING RANGE

- Platform Height (lowered) 1520mm
- Platform height (fully elevated) 2120mm
- SWL 200 kgs

STABILITY

- Manufactured with front mounted out-riggers to guarantee stability whether working with the platform in the lowered or fully elevated position.

Standards: JIG latest issue

REFUELLING

1 x 2.5" ISO45 aviation coupling, fitted for connection to the refuelling vehicle.

Main pipework constructed in 2" (50mm) Schedule 10 – 304 grade stainless steel.

Manually operated hydraulic pump actuates the platform offering flexibility of operating height between 1520mm and 2120mm above ground level.

Single 2" refuelling hose with underwing nozzle.

Option of adding additional pipework and a second refuelling hose and nozzle.

Integrated thermal relief system & collector tank

[FULL SPECIFICATION AVAILABLE UPON REQUEST](#)

WWW.FSLUK.COM

+44 1993 776564

sales@fsluk.com