



**FLIGHTLINE SUPPORT LTD**

## **FIXED HEIGHT REFUELLING STEPS**



### **INTRODUCTION**

Aluminium and stainless-steel construction. Designed to be robust, but light weight and easily manoeuvred by a single operator. 4 off heavy-duty 470mm diameter wheels are used to aid manual manoeuvrability.

Typical Dimensions: Length 4m, Height 2.8m, Width 1.9m

### **OPERATING RANGE**

- Fixed height platform at 1700mm
- Steps can be manufactured with the platform at a different height to suite a specific operation.

### **STABILITY**

- Manufactured with front mounted out-riggers to guarantee stability..

### **REFUELLING**

1 x 2.5" ISO45 aviation coupling, fitted for connection to the refuelling vehicle.

Main pipework constructed in 2" (50mm) Schedule 10 – 304 grade stainless steel.

Single 2" refuelling hose with underwing nozzle.

Option of adding additional pipework and a second refuelling hose and nozzle.

Integrated thermal relief system & collector tank

Standards: JIG latest issue

**FULL SPECIFICATION AVAILABLE UPON REQUEST**

**[WWW.FSLUK.COM](http://WWW.FSLUK.COM)**

**+44 1993 776564**

**[sales@fsluk.com](mailto:sales@fsluk.com)**